



Shell Helix *Ultra Professional* AV-L 0W-30

Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements.

Designed to meet the demanding requirements of particular high-performance engines, including VW, Audi and Porsche.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

▪ Fuel efficiency

Passes the VW fuel economy PV 1451 test.

Requires a minimum 2.5% fuel economy increase ¹.

Shell Helix Ultra Professional AV-L achieved up to a 3% fuel economy increase.

1 versus VW reference oil

▪ Volkswagen specific in-house tests

Passes the VW PV 1449 (T4) for viscosity increase and piston deposits.

Passes the VW PV 1452 (TDI) test for ring sticking and piston cleanliness.

Passes the VW seals tests.

Passes the VW PV 5106 cam and tappet wear test.

Passes the VW PV 1481 test for inlet valve deposits for direct injection gasoline engines.

Passes the VW DPF (diesel-particulate-trap) test for ash accumulation and pressure reduction.

Passes the VW RNT (radionuclide wear measurement) test for tappet and cam wear.

▪ Engine wear and durability

Passes Sequence IVB wear test (ASTM D8350) for valvetrain wear.

▪ Engine cleanliness

Passes the VW TDI piston cleanliness test (CEC-L-78-T-99).

Sequence VH sludge test (ASTM D8256) for engine sludge and varnish

▪ Soot control

Passes DV6C oil dispersion at medium temperature test (CEC L-106-16)

Main Applications

Shell Helix Ultra Professional AV-L 0W-30 for gasoline and diesel engines is approved against the technically challenging, top-tier VW 504.00/507.00 specifications.

Specifications, Approvals & Recommendations

▪ ACEA C3

▪ Porsche C30

▪ VW 504.00/507.00

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: <http://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Typical Physical Characteristics

Properties			Method	Shell Helix Ultra Professional AV-L 0W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	11.90
Kinematic Viscosity	@40°C	cSt	ASTM D445	58.70
Viscosity Index			ASTM D2270	204
MRV Viscosity	@-40°C	cP	ASTM D4684	18 900
Density		Kg/m ³	ASTM D4052	838.0
Flash Point		°C	ASTM D92	226
Pour Point		°C	ASTM D97	-51

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

■ Health and Safety

Shell Helix Ultra Professional AV-L 0W-30 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

■ Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Whilst we believe this data to be correct and reliable, we are not responsible for its interpretation and its use, nor should it be construed as a permission to use any product or process in breach of existing patents. This data does not constitute any warranty other than conformity of the product to current specifications published by the sellers or its suppliers. Any relevant legislation governing the use of the product should be observed.

Univar Solutions Local Conditions of Sale apply to sales of all products

Refer to the appropriate Safety Data Sheet for health, safety and environmental information